



✓ = standard

○ = optional

Technical specifications

Working areas

	075	100	150
X axis top face only	7 925 mm	10 085 mm	17 045 mm
X axis top face + ends	6 755 mm	8 915 mm	15 875 mm
Y and Z axes for machining on 2 faces of profile	583 mm x 360 mm		
Y and Z axes for machining on 3 faces of profile	454 mm x 360 mm		
C axis	-10° ; +370°		
D axis	-10° ; +190°		

Dynamic performance

X axis speed	85 m/min
--------------	----------

Profile positioning and locking

Vices with controlled and independent positioning	✓	✓	✓
Max number of vices	14	14	16
Transfer and automatically reclining stop	1 ✓ - 1 ○	1 ✓ - 1 ○	2
Central stop	○	○	○
Adjusting vice pressure with pressure gauge	✓	✓	✓
Multi-piece machining	○	○	✓
Pendular machining	○	○	○
Multi-piece pendular machining	○	○	○

Lubrication of mechanical component

Automatic lubrication of straight guide blocks and recirculating ball screw lead screws	✓	✓	✓
---	---	---	---



✓ = standard ○ = optional

Technical specifications

Electrospindle	075	100	150
Electrospindle 22 kW 24 000 rpm	✓	✓	✓
Rigid tapping	✓	✓	✓
Cooling	Liquid with refrigerator unit		
Tool collet	HSK E63		
Rated torque	20 Nm		
Tool magazine			
20-Position tool magazine mounted on the head	✓	✓	✓
Max blade diameter housed	500 mm		
Tool lubrication			
Minimum quantity lubrication	✓	✓	✓
Lubrocooling	✓	✓	✓
Additional Flowdrill lubrication system	○	○	○
Control and software			
24" screen	✓	✓	✓
Wireless bar-code reader	○	○	○
FSTCam4	✓	✓	✓
IoT ready	✓	✓	✓

